

INDUSTRIAL

Duplex



Heavy Duty Cast Iron Pumps
 Up to 48 CFM on Single Phase / 64 on Three Phase
 Single Pump Operation When Air Demand is Low, Providing Energy Savings
 Magnetic Starters and Alternator Mounted and Wired
 Two Pumps and Motors Provide Built in Back Up During Repair or Maintenance
 208-230 Single Phase or Tri-Voltage Three Phase Baldor Motors
 Disc Valves
 Heavy Duty Sheet Metal Beltguards
 ASME Tank and Safety Valves

Part Number	Tank Type	Weight (lbs)	Dimensions L x W x H (in)	Motor (hp)	Electrics (V/Phase/Hz)	Capacity (cfm @ 175psi)	Max Pressure (psi)	Pump Speed (rpm)
82-2349HAT208	120 gal Horizontal	1080	79 x 27 x 53	5	200/1/60	32	175	800
82-2349HAT	120 gal Horizontal	1078	79 x 27 x 53	5	230/1/60	32	175	800
82-2349HBT	120 gal Horizontal	1051	79 x 27 x 53	5	208-230/3/60	32	175	800
82-2349HBT460	120 gal Horizontal	1061	79 x 27 x 53	5	460/3/60	32	175	800
82-2379HAT	120 gal Horizontal	1388	79 x 27 x 51	7.5	200/1/60	48	175	600
82-2379HAT208	120 gal Horizontal	1404	79 x 27 x 51	7.5	200/1/60	48	175	600
82-2379HBT	120 gal Horizontal	1341	79 x 27 x 51	7.5	208-230/3/60	48	175	600
82-2379HBT460	120 gal Horizontal	1341	79 x 27 x 51	7.5	460/3/60	48	175	600
82-2309HBT460	120 gal Horizontal	1395	79 x 27 x 51	10	460/3/60	64	175	800
82-2309HBT	120 gal Horizontal	1395	79 x 27 x 51	10	208-230/3/60	64	175	800
82-2300HBT	200 gal Horizontal	1525	82 x 30 x 58	10	208-230/3/60	64	175	800
82-2300HBT460	200 gal Horizontal	1535	82 x 30 x 58	10	460/3/60	64	175	800

